

User Manual

Indoor FHD IP Camera



Model: C2M

Table of Contents

1 Overview.....	3
1.1 Key Features.....	3
1.2 Read before Use.....	3
1.3 Packing Contents.....	3
1.4 Physical Description.....	4
1.5 SD Card Management.....	5
1.6 Add Device: Connection via the Foscam App.....	5
1.7 Installation.....	5
2 Default Parameters.....	6
3 Specification.....	6

1 Overview

1.1 Key Features

- ◆ 2.0 Mega-Pixel
- ◆ H.264+/H.264 video Compression
- ◆ Supports 2.4GHz and 5GHz network
- ◆ Supports Human detection, Motion Detection and Sound Detection
- ◆ Compatible with free Foscam Video Management Software
- ◆ Compatible with free Foscam iOS and Android APP
- ◆ Supports Full Duplex two-way Audio
- ◆ Supports voice prompt
- ◆ Supports 256GB Micro SD Card storage(External)
- ◆ IR Range up to 8m(26ft)
- ◆ P2P Feature for Easy Remote Access
- ◆ Supports image snapshot
- ◆ Supports dual-stream
- ◆ Supports remote viewing & record from anywhere anytime
- ◆ Multi-level users management with password protection
- ◆ Supports multiple network protocols: IP, TCP, UDP, SMTP, FTP, DHCP, RTSP
- ◆ Supports Alexa
- ◆ Supports Google Assistant


1.2 Read before Use

Please first verify that all contents received are complete according to the Package Contents listed below. Before the Network Camera is installed, please carefully read and follow the instructions in the Quick Setup Guide to avoid damage due to faulty assembly and installation. This also ensures the product is used properly as intended.

1.3 Packing Contents

● Camera× 1	● Ethernet Cable× 1
● Quick Setup Guide × 1	● Expansion Screws× 1
● AC Adapter × 1	● Power Line × 1

1.4 Physical Description



Front panel:

- Induction IC
- LENS: Fixed focus lens
- Microphone: Built-in microphone.
- Micro SD Card slot: Supports up to 128GB SD card for storing the video.
- Magnetic Bracket: Adsorbing on a ferromagnetic object using a magnet on the base

Rear panel:

- Power Light: If the power supply works fine, the light will be on.
- LAN: 10/100 Mbps RJ-45 port for wired connection
- WPS/Reset
 - WPS: Push both WPS/Reset button on the camera and wireless router within 1 minute, the camera will connect to the wireless router automatically, in WPS process, the Network light will blink every 0.4 seconds;
 - Reset: Push and hold the WPS/Reset button for more than 10 seconds to set the camera to factory default, the Power light will blink every 0.4 seconds;
- Power: DC 5V/1A Power supply.

The flashing status of the Power/Network light are shown in the following table.

Flashing Status	Description
Flashing(red) every 0.4 seconds	Reset to take effect
Constant Flash(green)	Wired connection
Slow Flash(green) every 1.0 second	Wi-Fi connected
Flashing every(green) 0.4 seconds	WPS is connecting
Flashing every(green) 0.2 seconds	EZLink takes effect

1.5 SD Card Management

This camera supports Micro SD Card.

When you plug in the SD card during the camera work process, please reboot the camera again, or else the SD card might not work well.

On Foscam app go to the **Settings**→**Device Status**→**Device Status** page, you can see the SD card status.

1.6 Add Device: Connection via the Foscam App


Scan the QR code below to download and install the Foscam APP.



Please refer to the **Quick Setup Guide**.

1.7 Installation

Please refer to the **Quick Setup Guide**.



Step 1: Rotate the base of the camera until points a and b are aligned, this allows for the mounting plate be removed.

Step2: Install the mounting plate on a wall or ceiling with supplied fixing screws.

Step3: Align points a and b to insert the camera base to the mounting plate. Rotate so that points a and b no longer aligned, this attaches the camera securely to the base.

2 Default Parameters

Default network parameters

IP address: obtain dynamically

Subnet mask: obtain dynamically

Gateway: obtain dynamically

3 Specification

	ITEMS	C2M V6
Image Sensor	Sensor Type	High Definition Color CMOS Sensor
	Display Resolution	2.0Megapixels(1920x1080)
	Min. Illumination	0 Lux (With IR Illuminator)
Lens	Lens Type	f.2.8mm; F2.0
	Angle of view	Diagonal: 108.8°, Horizontal: 98.2°, Vertical: 53.1°
Video	Image Compression	H.264+/H.264
	Resolution	1080P(1920x1080) 25fps,720P(1280 x 720), VGA(640 x 480)
	Stream	Dual stream
	Image Adjustment	The brightness, contrast, saturation, sharpness are adjustable
	Flip Image	Flip and mirror
	Infrared Mode	Automatic or manual
Audio	Night Visibility	9pcs IR-LEDs, night vision range up to 8 metres
	Input/Output	Supports Two-way Audio
Network	Audio Compression	PCM/AAC
	Ethernet	One 10/100Mbps RJ45 port
	Wireless Standard	2.4G/5G dual-band, IEEE802.11b/g/n/ac
	Data Rate	IEEE802.11b: 11Mbps(Max.); IEEE802.11g: 54Mbps(Max.); IEEE802.11n: 150Mbps(Max.). IEEE802.11ac: 433Mbps(Max.).
	Wireless Security	WPA, WPA2
	Wireless Setup	Supports QR Code+Wave wireless setup
	Network Protocol	IP, TCP, UDP, SMTP, FTP, DHCP, RTSP
	Remote Access	P2P
System Requirements	Operating System	Microsoft Windows (Foscam VMS), MacOS (Foscam VMS), Android (Foscam app), iOS (Foscam app)
Other Features	Motion Detection	Alarm via E-Mail, FTP and Foscam app when an event is detected
	Sound Detection	Alarm via E-Mail, FTP and Foscam app when an event is detected

	Human Detection	Alarm via E-Mail, FTP and Foscam app when an event is detected
	WDR	Improve image clarity in complex scenario
	Zoom	6X digital zoom function
	User Accounts	Three levels user role
	Storage	Support max. 256GB Micro SD card, local and FTP storage,Foscam cloud storage
	Intelligent Assistant	Supports Alexa, Google Assistant
Power	Power Supply	DC 5V/1A
	Power Consumption	<4.8W
Physical	Color	Black/White
	Dimension(mm)	70(L)*70(W)*120(H)mm
	Net Weight	125g
Environment	Operating Temperature	-10°C ~ 40° (14°F ~ 104°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temperature	-20°C ~ 60° (-4°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
Certification	CE, FCC, RoHS,WEEE,RCM	

For other parts, please refer to the “FOSCAM Camera User Manual”